



## Cheetah



### Day and night performance

HIKMICRO Cheetah Digital Night Vision Monocular can be easily transformed into a scope and performs well under any lighting condition. Its advanced 2560 x 1440 HD sensor and 1920 x 1080 OLED display are capable of capturing every object in great detail and with rich clarity.

I	MODEL	RANGE	FOV	MAG	SENSOR	RRP
	C32FS KIT	400m	8.1° × 6.1°	2.7-21.6	2560×1440.850nm	\$1,299
뽔	C32FSL KIT	400111	0.1 ^ 0.1	2.7-21.0	2300/1440, 83011111	\$1,799

\*fixed at base magnification in clip-on mode \*\* Ballistic Calculator features on all LRF Models





#### Compact yet powerful

High thermal sensitivity, perfect detail recognition. Every detail matters when identifying targets. Less than 20 mK NETD helps identify small details of objects from their background easily and clearly even in the hardest weather and low- light conditions.

	MODEL	RANGE	FOV	MAG	SENSOR	RRP
PANTHER 2.0	PQ50L 2.0	2600m	8.8° × 7°	2.6 - 20.8	640 × 512, 12 µm	\$7,999
	PQ35L 2.0	1800m	12.5° × 10°	1.77 - 14.16	NETD < 20mK	\$7,299
	PH50L 2.0	2600m	5.3°×4°	4.22 - 33.76	384 × 288, 12 µm	\$5,899
	PH35L 2.0	1800m	7.5° × 5°	2.96 - 23.68	NETD < 20mK	\$4,999

\*\* Ballistic Calculator features on all LRF Models

## **EXPLORER**

SMARTPHONE THERMAL CAMERA

### Ultimate in Portability

Thermal Camera for Android Smartphone, the E20PLUS is designed for consumer applications for outdoor activities such as bird watching, hiking, camping, sports & concerts.

MODEL	RANGE	FOV	MAG	SENSOR	RRP
<b>E20</b>	970m	18.1° × 13.6°	2x	256 × 192 NETD < 50mK	\$599.99



### TRAIL CAMERA

### Powerful & Robust

The HIKMICRO M15 wildlife camera is a powerful and robust 4G-equipped camera ideal for wildlife observation and is an extremely useful device for hunting and a variety of other outdoor activities.

MODEL	RANGE	FEATURE	SENSOR	RRP
M15	25m Identification Range	.5 Second Trigger Speed	1080P 940nm	\$399.99
SP5000	SOLAR PANEL - Powerk	pank		\$199.99

Includes BONUS 32gb SD Card





#### **Enhanced Resolution**

The Habrok Pro & 4K models combine thermal and digital optical channels, enhancing outdoor experiences. Compact like traditional binoculars but packed with advanced tech. Detect in thermal, view in optical, and record to built-in memory.

	MODEL	RANGE	FOV	MAG	SENSOR	RRP
	HX60L	3100m/400m	7.3°×4.1° 14.6°×8.8°	D  5.5-22 T  2.6- 26	1280×1024, 12µm NETD < 18mK	\$10,999
	HQ50L	2600m/400m	7.3°×4.1° 8.8°×5.3°	D  5.5-22 T  4.3 - 25.8	640×512, 12µm NETD < 15mK	\$7,499
HABROK PRO 8 4K	HQ35L4K	1800m/400m	12.5°×10.1 6.9°×4.1°	D 2.9 - 23.2 T 3-24	640×512, 12 µm NETD < 20mK	\$6,799
	HH35L	10001117 400111	13.9°×7.8° 7.5°×5.7°	D 2.9 - 23.2 T 4-32	384×288, 12 µm NETD < 20mK	\$4,999
	HE25L	1200m/400m	6.9°×4.1° 7°×5.3°	D  5.5-22 T  4.3 - 17.2	256×192, 12µm NETD < 35mK	\$2,999

All Habrok range also available in a 940nm



### All-in-one Solution

In combination with thermal camera, digital day & night camera, and laser rangefinder, the ultimate innovative RAPTOR series binocular provides unprecedented observation capability in thermal or true living color,up close or from a distance, during day or night in all weather conditions.

	MODEL	RANGE	FOV	MAG	SENSOR	RRP
RAPTOR	RQ50LN		8.8° × 7° 3.4-54.4	640 × 512, 12 µm	\$8,999	
	RQ50L	2000	0.0 × /	3,4-34,4	NETD < 20mK	\$8,999
	RH50LN	2600m	5.3°×4°	5.7-91.2 384 × 288, 12 µm	\$6,999	
	RH50L		5.5 ×4	5.7-91.2	NETD < 20mK	\$6,999

**NZ Office number** 03 789 4112

NZ Office Email ordersnz@huntsmanoptics.com























THE ULTIMATE IN
THERMAL AND NIGHT VISION SOLUTIONS



# **Lynx** 2.0 & THERMAL MONOCULAR



### Lightweight & Compact

Compact and light with a very comfortable and robust feel to it, the LYNX Monocular has the ultimate thermal performance housed in a small package. With advanced engineering, the refresh rate is smooth and fast - eliminating the need for recalibration as you scan your hunting zone.

	MODEL	RANGE	FOV	MAG	SENSOR	RRP
LYNX 2.0	LH35 2.0	1800m	7.5°×5.7°	3.3 - 26.4		\$2,699
	LH25 2.0	1200m	10.5° × 7.9°	2.4 - 19.2		\$2,399
	LH19 2.0	900m	13.7°× 10.3°	1.8 - 14.4	384 × 288, 12µm NETD < 20mK	\$2,199
	LH15 2.0	750m	17.5° × 13.1°	1.4 - 11.2	NETD (ZOTTIK	\$1,899
S	LE15 S	750m	11.7°×8.8°	2.2 - 17.6	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	\$1,199
ž	LE10 S	500m	18°×13.6°	1.5 - 12	256 × 192, 12µm NETD < 35mK	\$999.99
7	LC06 S	250m	24.7°×18.7°	1-4	(	\$699.99





### Industry Leading Thermal Performance

The Falcon thermal monocular combines an advanced NETD<15 mK sensor with an F0.9 lens, ensuring exceptional imaging even in tough weather. The Falcon boasts a durable design, intuitive controls, and a 5-hour battery. Unique "Image Pro mode" enhances detail, supported by 64GB internal storage.

MODEL	RANGE	FOV	MAG	SENSOR	RRP
FQ50L 2.0	2600m	8.8° × 7°	25 200		\$5,699
FQ50 2.0	2600m	8.8 × /	2.6 - 20.8	640 × 512, 12 µm NETD < 15mK	\$4,999
FQ35 2.0	1000	12.5°×10°	1.8 - 14.4		\$4,199
FH35	1800m	7.5° × 5.7°	3 - 24	384 × 288, 12 µm NETD < 20mK	\$2,999



### Remarkable image quality

THERMAL MONOCULAR

This compact spotter is equipped with a powerful, high-sensitivity NETD<15 mK thermal detector, which captures exceptionally fine detail. The result is a vivid, layered image, which doesn't just make it easy to spot and identify target quarry but also gives a very clear view of the surrounding landscape.

	MODEL	RANGE	FOV	MAG	SENSOR	RRP
CONDOR	CQ50L 2.0	2600m	8.7° × 7°	3 - 24	640 × 5 12, 12 µm	\$5,299
	CQ35L 2.0	1800m	12.5° × 10°	2 - 16	NETD < 15mK 384 × 288, 12 µm	\$4,799
	CH35L	1600111	7.5° × 5.6°	3.5 - 28		\$3,899
	CH25L	1200m	10.5° × 7.9°	2.5 - 20	NETD < 20mK	\$3,299

### Stellar 3.0 THERMAL TUBE SCOPE



### Traditional tube with powerful performance.

The Stellar 3.0 Thermal Scopes feature high-resolution detectors (up to 1280 × 1024), 2560 × 2560 OLED displays, and NETD<15 mK sensitivity. With up to 3100 m detection range, built-in laser rangefinder, ballistic calculation, and 10-hour battery life, they offer precision and reliability for field and forest hunting.

	MODEL	RANGE	FOV	MAG	SENSOR	RRP
LAR 3.0	SX60L 3.0	3100m	14.6° × 11.7°	2.5 - 28.5	1280 × 1024, 12 µm NETD < 18mK	\$10,999
	SQ50L 3.0	2600m	8.8° × 7°	3.6 - 26.6	640 × 512, 12 µm	\$7,499
	SQ35L 3.0	1800m	12.5°×10°	2.5 - 24.5	NETD < 15mK	\$6,999
STE	SH50L 3.0	2600m	5.3° × 4°	6 - 24		\$5,999
	SH35L 3.0	1800m	7.5° × 5.7°	4.2 - 24.2	384 × 288, 12 µm NETD < 15mK	\$4,799
	SH35 3.0		7.5 ~ 5.7	7.2 27.2		\$3,999



### Born for Low Light

The HikMicro Alpex with advanced sensor technology and image processing to deliver a detailed, full colour image throughout the day automatically adjusting to twilight and continuing to display an amazing full colour image up until total darkness.

	MODEL	RANGE	FOV	MAG	CMOS RESOLUTION	RRP
PEX 4K	A50EL			3.5 - 28 3840 × 2160 \$1	\$1,799	
	A50EL KIT	1000m	8.8° × 5°		\$1,999	
	A50E		0.0 ^ 3		\$1,499	
Ā	A50E KIT					\$1,699
	A40EL				\\	\$1,499
	A40E		10.7° × 6.1°	3.5 - 20.5	1920 × 1080	\$1,199

\*\* Ballistic Calculator features on all LRF Mod





#### The 1440×1080 HD CMOS sensor gives a ground-breaking image in both day and night. Making the HikMicro Alpex the obvious winner when it comes to LOW-LIGHT HUNTING.

	MODEL	RANGE	FOV	MAG	CMOS RESOLUTION	RRP
Ä	A50T-S	600m	77°×5.8°	3.5 - 14	1920 × 1080	\$1,099
ALF	<b>A50T-S</b> KIT	000111	7.7 ^ 3.8	3.5 - 14	1920 ^ 1000	\$1,399

#### www.huntsmanoptics.com







## Thunder 2.0

THERMAL SCOPE

### Impressive Detail Recognition

With an extremely high thermal sensitivity (NETD<20mK) detector combining a powerful thermal camera of up to 640x512 @12µm @ F1.0, it ensures informative images and an enhanced identification capability even under the slightest temperature differences.

	MODEL	RANGE	FOV	MAG	SENSOR	RRP
$\mathbb{N}$	TQ50 2.0	2600m	8.7° × 7°	2.6 - 20.8	640 × 512, 12 µm	\$6,799
i /	TQ35 2.0	1800m	12.5° × 10°	1.8 - 14.6	NETD < 20mK	\$5,599
<b>[</b> ]	TH35P 2.0		7.5° × 5.7°	3 - 24	384 × 288, 12 µm NETD < 20mK	\$4,499
	TH25P 2.0	1200m	10.5°×7.9°	2.2 - 17.6		\$3,999
THUNDER	TE25 2.0		7°× 5.3°	3.3 - 26	256 × 192, 12µm NETD < 35mK	\$2,399
	TE19 2.0	1000m	9.2°× 6.9°	2.5 - 19.8		\$1,899

### Thunder 3.0

THERMAL CLIP-ON

### Clip-On Versatility

These thermal monoculars boast high-resolution detectors @ 640 × 512, 1920 × 1080 OLED displays, and NETD < 15 mK sensitivity, offering detection ranges up to 2600 m. With a 6-hour battery life and 1000 g shock resistance, they deliver top-tier performance in any environment.

MODEL	RANGE	FOV	MAG	SENSOR	RRP
TQ50CL 3.0	2600m	8.8° × 7°	×1*	640 × 512, 12 µm NETD < 15mK	\$6,499
TH35C 3.0	1800m	7.5° × 5.7°	×]*	384 × 288, 12 µm NETD < 15mK	\$4,499

\*fixed at base magnification in clip-on mode

### **Thunder ZOOM** 2.0

THERMAL SCOPE

### **Dual FOV Technology**

With a 2.2x to 34.6x large magnification realized by the 384 detector @20mK, TH50Z 2.0 is the perfect match for both wooded and open field areas. A F0.8 large aperture also strengthens your viewing ability of objects.

	MODEL	RANGE	FOV	MAG	SENSOR	RRP	
4 2.0	TQ60Z 2.0	3000m	12.5° × 10°/ 7.3° × 5.9°	1.8-14.6/ 3.1 - 25	640 × 512, 12 µm NETD < 20mK	\$7,699	
00Z	TH50Z 2.0	2600m	10.5° × 7.9°/ 5.3° × 4°	2.2 - 17.4 / 4.3 - 34.6	384 × 288, 12 µm NETD < 20mK	\$5,299	

NZ Office number 03 789 4112





**HIKMICRO**